

Date: ___ - ___ - ___

CUSTOMER INFORMATION

Clinician Name: _____ Facility / Clinic: _____
 Preferred Contact Method: _____ Bill to Account #: _____ PO #: _____
 Email Address: _____ Shipping Address Line 1: _____
 Phone: _____ Shipping Address Line 2: _____
 City: _____ State: _____ Zip Code: _____

SHIPPING INFORMATION

Carrier: UPS FedEx Method: Ground 3-Day 2-Day
 Next Day Next Day Saver

PATIENT INFORMATION

Amputation Side: Left Right Bilateral
*Requires separate order forms
Indicate side on each form.

Patient ID / Last Name: _____
 K-Level: K1 K2 K3 K4
 Height: _____ ft. _____ in.
 Weight: _____ lbs.
 Foot Size: _____ cm

PRODUCT INFORMATION

SOCKET MATERIAL

- Carbon from Cast
CS-DSTF-302
- Carbon from CAD
CS-DSTF-303

LOCK OPTIONS

- Genesis Bulldog Lock
CS-DSAD-425
- Bulldog Lanyard
CS-DSAD-431

SOCKET SPECIFICATIONS

SOCKET FINISH	INSERT
CARBON	BLACK FLEXIBLE INNER

REVOFIT® STYLE

POSTERIOR GAP

REVOFIT® REEL PLACEMENT

The reel will be positioned at the distal, anterior-medial aspect of the socket. This placement will blend naturally with the overall curve of the socket.

REVOFIT® GAP CUTOUT LOCATION & SIZE

The gap cutout will be positioned in the center of the posterior aspect of the socket.

The shape resembles a keyhole, with the narrow part at the top.
 The narrowest part of the cutout will be ~1 inch (2.5 cm) wide.
 The opening will then widen to reveal the inner flexible liner of the socket.
 The length will extend distally to an appropriate depth that allows the socket to function properly for limb compression.

Important Note: While we strive to follow these placement standards, the ultimate location of the dial and window may be adjusted slightly to ensure all components fit comfortably within the space limitations of your socket. This ensures optimal functionality and user experience.

NOTES:

